

# SUMNER

## SERIES 2412 CONTRACTOR LIFT



- ✓ A super compact 12 ft (3.6m) lift
- ✓ 400 lb (180 kg) lifting capacity
- ✓ One piece construction –no loose pieces
- ✓ Easily portable for one person operation
- ✓ Fits most SUVs and vans



### The perfect lift for:

- HVAC contractors
- Electrical contractors
- Industrial maintenance
- Steel erectors

# SERIES 2412 LIFT



### Handle

Use convenient handle for "hand truck" mobility and to position lift at point of use.



### Compact Storage

Forks remove and legs reposition for space saving storage.



Fits in Most Vans

### Winch

Coffee grinder style winch features auto-braking and detachable winch handles.

### Roller Wheels

Handy wheels located to ease rolling into vehicles for transportation.

### 8" (20 cm) Non-marring Wheels

### Wheel Brake

Fast action, foot actuated wheel brake prevents lift from moving.

## 2412 Lift (part number 784750)

Height max. (forks up)	13.0'	3.9 m
Height max (forks down)	12.0'	3.6 m
Lift capacity	400.0 lb	180.0 kg
Height stowed	62.8"	159.4 cm
Length stowed	23.0"	58.4 cm
Length operating	48.0"	121.9 cm
Width stowed	26.4"	67.1 cm
Width operating	26.4"	67.1 cm
Winch cranks per foot	8	(24/m)
Basic weight	195 lb	88.5 kg



# ...Check the features!

# SUMNER®

## Pulley Guards

Contain load cable  
...line cannot come off.

## Inside-Mast Cable Feed

Cable feeds inside mast,  
removed from the  
operator for safety  
-similar to the 2000 and  
2100 Series Lifts.



## Fork Storage

Forks tuck between  
mast and mast braces  
for out of the way  
storage.

## Reversible Forks

Two plunger pins  
permit quick release  
of forks. Forks may  
be removed for  
storage or reversed  
for added height.



## Optional Fork Extension

Forks may be  
extended from  
23.3" (59.2cm) to  
29.8" (75.7cm).



## Double Row Casters

Two 3" (7.5 cm) casters  
permit easy handling of  
heavy loads.




## Ideal for Compact Storage

No tools or loose hardware to worry about. Leg lock  
mechanism releases with plunger pin and slides on base leg.



Leg roller allows unit to  
wheel in stored position.





## Optional features available for the Series 2412 Lift

### Cable Brake (part no. 784755)

Each mast and carriage can have a factory installed, gravity actuated safety brake which holds loads in place in the event cable goes slack.



### Fork Extension (part no. 784695)

With the push of a button, forks may be extended from 23.3" (59.2cm) to 29.8" (75.7cm). When using the fork extensions the weight capacity reduces to 200 lb (90 kg), as is clearly marked on the extended forks. A second button returns the extension for storage inside forks.

### Pipe Cradle (part no. 783705)

Great for air ducts or other HVAC applications. Slides over forks. Packaged two per set.

